

CRT	Size (Diagonal: 19 (48.3cm), 29 mm neck
Viewable Image Size	18" (45.7cm)
Pre-set Display Area	Default: 346mm x 260mm Overscan:366x 274mm
Dot Pitch	(D) 0.25mm, (H) 0.21mm
Scan Frequency	Horizontal: 30K~98Kz Vertical: 50~160Hz
Video Dot Clock	200MHz
Compatibility	VESA, UXGA, SXGA, XGA, SVGA, VGA
Signal Input	Video: 0.7Vp-p, RGB analog
Maximum Resolution	1600 x 1200 @ 75Hz
Factory Pre-set Mode	8
User Programmable	20
Power Source	Universal 100~240 Vac, 50Hz / 60Hz
Power Consumption	130 Watts (Max.)
EPA ENERGY STAR ®	Yes, Off Mode 3W
Video Signal Connectors	15-pin mini D-sub Male
Front Panel Controls	4 OSD Buttons ,Power On/Off
OSD Function	Contrast, Brightness, Zoom, H-size, H-center, V-size, V-center, Pincushion, Trapezoid, Pin-balance, Parallelogram, Rotation, 6500K, 9300K, User's Color, Degauss, H/V Moiré Reduce, Recall, Language(English, German, French, Spanish, Italian), Exit
Base Operation	Tilt: -5°/+15° Swivel: -45° / +45°
Plug & Play	VESA DDC1/2B
Emissions Standard	MPRII
Regulations	UL, FCC, CSA, CE
Other Features	n/a
Dimensions (WxHxD mm)	Monitor: 446 x 436 x 455; Carton: 540 x 530 x 570
Dimensions (WxHxD inches)	Monitor: 17.6 x 17.2 x 17.9; Carton: 21.3 x 20.9 x 22.46
Monitor Dimensions without Base	n/a
Weight	Net: 40.1lbs (18.2kg); Gross: 46.7lbs (21.2kg)
Loading Qty without Pallet	n/a
Loading Qty with Pallet	n/a
Warranty	3 Year Parts & Labor
UPC Code	663555007742